



DIN 7753 Teil Part 1/ISO 4184/BS 3790

USA-Standard RMA/MPTA

Profil Profile SPB	Profil Profile SPC	Profil Profile 8V/25N	
Richtlänge Datum length ISO (mm)	Richtlänge Datum length ISO (mm)	Riemenbezeichnung Belt no. (Zoll inch)   (Außenlänge Outside length mm)	
BM BQ = 10 Stück pieces 1500 1600 1700 1800 1900 2000 2120 2240 2360 2500 2650 2800 3000 3150 3350 3550 3750 4000 4250 4500 4750 5000 BM BQ = 5 Stück pieces 5300 5600 6000 6300 6700 7100 7500 8000	BM BQ = 10 Stück pieces 2000 2120 2240 BM BQ = 5 Stück pieces 2360 2500 2650 2800 3000 3150 3350 3550 3750 4000 4250 4500 4750 5000 BM BQ = 3 Stück pieces 5300 5600 6000 6300 6700 7100 7500 8000 8500 9000	BM BQ = 1 Stück piece 8V 1600   25N 4064 8V 1700   25N 4318 8V 1800   25N 4572 8V 1900   25N 4826 8V 2000   25N 5080 8V 2120   25N 5385 8V 2240   25N 5690 8V 2360   25N 5994 8V 2500   25N 6350 8V 2650   25N 6731 8V 2800   25N 7112 8V 3000   25N 7620 8V 3150   25N 8001 8V 3350   25N 8509 8V 3550   25N 9017	

**Anfertigungsware. Non stock items.**

Weitere Abmessungen und Profile auf Anfrage. Further sizes and profiles on request.

Maximale Fertigungslänge <i>Maximum manufacturing length: 8000 mm</i> <b>Mindest-Abnahmemenge</b> <i>Minimum production quantity:</i> 1500 mm – 1800 mm = 25 Stück pieces über over 1800 mm = 23 Stück pieces  Gewicht Belt weight: ≈ 0,206 kg/m	Maximale Fertigungslänge <i>Maximum manufacturing length: 10000 mm</i> <b>Mindest-Abnahmemenge</b> <i>Minimum production quantity:</i> ab from 2000 mm = 16 Stück pieces  Gewicht Belt weight: ≈ 0,389 kg/m	Maximale Fertigungslänge <i>Maximum manufacturing length: 12065 mm L<sub>a</sub></i> <b>Mindest-Abnahmemenge</b> <i>Minimum production quantity:</i> ab from 4064 mm L <sub>a</sub> = 14 Stück pieces  Gewicht Belt weight: ≈ 0,603 kg/m
---	--	---